



Recifier Reverse Voltage 50V to 1000V
MSB

Features

- Glass passivated junction
- The plastic material used carries Underwriters Laboratory flammability recognition 94V-0
- Suge overload ratings to 50 amperes peak
- Ideal for printed circuit board application
- High temperature soldering guaranteed 265°C/10 seconds at 5 lbs(2.3kg)tension

Mechanical Data



Case:Molded plastic

Terminals:Platde leads solderable per MIL-STD-750, Method 2026

Polarity:Polarity symbols molded or Marked on body

Mounting Position:Any

Weight:0.007ounce,0.2 grams(approx)



SPACING

Maximum Ratings & Thermal Characteristics

Rating at 25°C ambient temperature unless otherwise specified,Resistive or inductive load,60HZ.

For Capacitive load derate current by 20%

Parameter	Symbol	RMSB	RMSB	RMSB	RMSB	RMSB	RMSB	RMSB	unit
		601	602	603	604	605	606	607	
Maximum repetitive peak reverse voltage	VRRM	50	100	200	400	600	800	1000	V
Maximum RMS bridge input voltage	VRMS	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	VDC	50	100	200	400	600	800	1000	V
Maximum average forward rectified output current at TA=40°C	IF(AV)	6.0							A
Maximum instantaneous forward voltage drop per leg at 3.0A	VF	0.95			1.25				V
Peak forward surge current single sine-wave superimposed on rated load (JEDEC Method)	IFSM	125							A
Maximum DC reverse current at ratde TA=25°C DC blocking voltage per element TA=125°C	IR	10 500							UA
Maximum reverse recovery time at	T _{rr}	150				250	500		nS
Rating for fusing(t<8.3ms)	I ² t	60							A ² sec
Typical thermal resistance per element(1)	ReJA	110							°C/W
Typical thermal resistance per element(2)	Cj	25.0							PF
Operating junction and stroage temperature range	TJ, TSTG	-55to+150							°C

Notes:(1)Thermal resistance from Junction to Ambemt on P.C.board mounting.

(2)Measured at 1.0MHz and applied reverse voltage of 4.0 volts.



RMSB601 thru RMSB610

6.0A Single-Phase Fast Recovery Bridge Rectifiers



Rating and Characteristic Curves (TA=25°C Unless otherwise noted)

FIG.1-FORWARD DERATING CURRENT




FIG.2-MAXIMUM NON-REPETITIVE SURGE




FIG.3-TYPICAL FORWARD





FIG.4-TYPICAL REVERSE






Ordering Information(Example)

PREFFREN P/N	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
RMSB601~ RMSB607 RMSB6005~ RMSB610	Approximate 0.20	3000	6000	36000	REEL

Suggested pad layout



Dimensions in millimeters

Unit:mm	
DIM	MIN
P0	5.12
P1	8.73
L	1.2
W	2.22